



# MAXAM

# MS705

## CONSTRUCTION PRO

Applications:



Premium 3-stage solid skid steer tire. Ideal for the most extreme OTR and construction applications. Extra deep tread allows for 3 to 5 times longer tire life vs pneumatic.

- 3-stage, 100% rubber construction:
  - Ultra cut and wear resistant tread compound
  - Heat resistant cushion center compound
  - Pure rubber base compound
  - Internal steel ring reinforcement eliminates wheel slip

- Zero maintenance solid construction:
  - No flats due to punctures or sidewall damage
  - No routine air pressure checks
- Self-cleaning R4 tread pattern designed for maximum chunk resistance
- Aperture (AP) sidewall configuration designed to provide soft ride
- Smooth tread available to maximize tire life

Size	Alt. Size	Tread	Sidewall	Rim	O.D.		S.W.		T.D.		L.C.C. (lbs/kg)		L.I.
					in	mm	in	mm	in	mm	5 mph	10 mph	
10-16.5	31x10-20	SM	ST	7.5x20	31.0	787	10.0	254	1.7	43	7850	3550	152A2
					31.0	787	10.0	254	1.7	43	6950	2280	
		R4	AP	7.5x20	31.0	787	10.0	254	1.7	43	7850	3550	148A2
					31.0	787	10.0	254	1.7	43	6950	2280	
12-16.5	33x12-20	SM	ST	7.5x20	33.0	838	11.0	279	2.2	56	8800	4000	156A2
					33.0	838	11.0	279	2.2	56	7850	3550	
		R4	AP	7.5x20	33.0	838	11.0	279	2.2	56	8800	4000	152A2
					33.0	838	11.0	279	2.2	56	7850	3550	
14-17.5	36x14-20	R4	ST	7.5x20	36.0	914	13.7	348	2.9	72	9650	4375	159A2
		R4	AP	7.5x20	36.0	914	13.7	348	2.9	72	8550	3875	155A2

