



MAXAM MS708

OTR PRO

Applications:



Premium 3-stage solid OTR loader tire. Ideal for the most extreme OTR and construction applications. Extra deep tread allows for 3 to 5 times longer tire life vs pneumatic. Mounts on standard multi-piece earthmover rims.

- 3-stage, 100% rubber construction:
 - Ultra cut & wear resistant tread compound
 - Heat resistant cushion center compound
 - Pure rubber base compound

- Internal hexagonal bead rings eliminate wheel slip
- Zero maintenance solid construction:
 - No flats due to punctures or sidewall damage
 - No routine air pressure checks
- Self-cleaning R4 tread pattern designed for maximum chunk resistance
- Aperture (AP) sidewall configuration designed to provide soft ride
- Smooth tread available to maximize tire life

Size	Tread	Sidewall	Rim	O.D.	S.W.	T.D.	L.C.C. (lbs/kg)		L.I.	
				in mm	in mm	in mm	5 mph 10 kph	10 mph 15 kph		
17.5-25	SM	ST	14.00	53.0	17.8	6.1	24700	17890	192A2	
		AP		1346	452	155	11200	8100	188A2	
	TR	ST	14.00	53.0	17.8	6.1	24700	17890		192A2
		AP		1346	452	155	10090	7300	188A2	
	20.5-25	SM	ST	17.00	58.8	20.8	7.4	35300	25570	204A2
			AP		1493	528	188	16010	11600	200A2
TR		ST	17.00	58.8	20.8	7.4	35300	25570	204A2	
		AP		1493	528	188	30900	22380	200A2	
23.5-25		SM	ST	19.50	64.0	23.5	8.6	44100	31950	212A2
			AP		1625	597	218	20000	14500	208A2
	TR	ST	19.50	64.0	23.5	8.6	44100	31950	212A2	
		AP		1625	597	218	20000	14500	208A2	
	26.5-25	SM	ST	22.00	68.4	27.0	9.5	53600	38830	219A2
			AP		1737	686	241	24300	17600	215A2
TR		ST	22.00	68.4	27.0	9.5	53600	38830	219A2	
		AP		1737	686	241	21800	15800	215A2	
29.5-25		SM	ST	25.00	73.0	29.7	10.4	66000	47810	226A2
			AP		1854	754	264	30000	21700	222A2
	TR	ST	25.00	73.0	29.7	10.4	66000	47810	226A2	
		AP		1854	754	264	26500	19190	222A2	