



MAXAM

MS902

BACKHOE - INDUSTRIAL SERVICE

Modified R1 tread pattern for excellent traction and flotation in soft underfoot conditions.

- Tread design optimized with self-cleaning mud breakers
- Center tie bar reduces vibration during over-the-road driving
- Deep undertread for improved puncture resistance
- Wear and cut resistant compound

Applications:



Size	P.R.	Type	Rim	O.D.	S.W.	T.D.	Infl. P.	Position	L.C.C. (lbs/kg)		L.I.
				in mm	in. mm	32nds mm	psi KPa		5 mph 10 kph	25 mph 40 kph	
12.5/80-18	12	TL	9.00	38.8 986	13.4 340	26 21	58 400	-	7500 3400	6000 2725	143A8
	14	TL	9.00	38.8 986	13.4 340	26 21	62 425	-	8000 3650	6400 2900	145A8
15.5/80-24 (400/80-24)	12	TL	13.00	50.0 1270	15.5 394	35 28	44 300	-	11550 5220	8250 3750	154A8
	14	TL	13.00	50.0 1270	15.5 394	35 28	51 350	-	12320 5600	8800 4000	156A8
	16	TL	13.00	50.0 1270	15.5 394	35 28	58 400	-	13510 6100	9650 4375	159A8
16.5/85-24	12	TL	13.00	52.0	16.4	35	40	FREE	14700	10500	162A8
				6670	4750	DRIVE	10360	7400			
	1321	417	28	275	4700		3350	150A8			
	14	TL	13.00	52.0	16.4	35	48	FREE	15960	11400	165A8
				7240	5150	DRIVE	11270	8050			
	1321	417	28	330	5100		3650	153A8			
16	TL	13.00	52.0	16.4	35	55	FREE	17220	12300	168A8	
			7810	5600	DRIVE	12320	8800				
1321	417	28	380	5600		4000	156A8				
16.5/85-28	10	TL	W13	54.9	15.2	35	33	FREE	12320	8800	156A8
				5600	4000	DRIVE	8610	6150			
1394	386	28	225	3900	2800		144A8				

