



# MAXAM MS905

## GRADER / TELEHANDLER

Aggressive R4 tread pattern for use on graders and telehandlers where high traction is required.

- Tread design optimized with self-cleaning mud breakers
- Center tie bar reduces vibration during over-the-road driving
- Deep undertread for improved puncture resistance
- Wear and cut resistant compound

Applications:



Size	P.R.	Type	Rim	O.D.	S.W.	T.D.	Infl. P.	L.C.C. (lbs/kg)		L.I.
				in mm	in. mm	32nds mm	psi KPa	5 mph 10 kph	25 mph 40 kph	
13.00-24	12	TL	8.00TG	50.2	13.7	32	44	9550	6000	143A8
				1276	349	25	300	4360	2725	
	14	TL	8.00TG	50.2	13.7	32	51	10500	6600	146A8
				1276	349	25	350	4800	3000	
	16	TL	8.00TG	50.2	13.7	32	58	11400	7150	149A8
				1276	349	25	400	5200	3250	
14.00-24	12	TL	8.00TG	53.0	14.5	32	36	10390	6800	147A8
				1346	368	25	250	4700	3075	
	16	TL	8.00TG	53.0	14.5	32	51	12300	8050	153A8
				1346	368	25	350	5580	3650	

