



MAXAM MS306

E3

A high traction E3 pattern for use in dump truck applications.

- Excellent traction in all off-road conditions
- Deep undertread for improved puncture resistance
- Reinforced all-steel radial casing provides superior loading performance
- Wear and cut resistant tread compound
- Wide, flat footprint profile for maximum stability and wear

Applications:



Size	Rating	Type	Rim	O.D.	S.W.	T.D.	Infl. P.	L.C.C. (lbs/kg)	Infl. P.	L.C.C. (lbs/kg)	L.I.
				in mm	in mm	32nds mm	psi KPa	30 mph 50 kph	psi KPa	5 mph 10 kph	
13.00R25	★★★	TT	8.50/1.3	51.2	13.2	31	102	10700	138	18700	163B/182A2
			10.00W	1300	336	25	700	4875	950	8500	
14.00R24	★★★	TT	10.00W	53.5	14.4	34	102	12800	138	22000	169B/188A2
			8.5/1.3	1359	365	27	700	5800	950	10000	
14.00R25	★★★	TT	10.00/2.0	53.5	14.4	34	102	12800	138	22000	169B/188A2
			8.5/1.3	1359	365	27	700	5800	950	10000	
16.00R25	★★★	TT	11.25/2.5	58.5	17.1	35	102	16100	138	26800	177B/195A2
			8.5/1.3	1487	433	28	700	7300	950	12150	

